



Modelo Máquina Termofusora Dígital / **FYD40**



FYD40

Las Maquinas de fusión digitales se utilizan para conectar PP-R, PE, PB, PVDF, tuberías y accesorios.

Termofusión y Riego Perú SAC | RUC 20604167796



Technical Data

FYD40

Rated Voltage:	110V/220V
Rated Frequency:	50/60Hz
Rated Power:	600W
Working Temp:	220°C-260°C
Temp.Tolerance:	≤2°C(professional test method)
Warning Temp:	set temperature +20°C
Environment Temperature:	-5°C-45°C
Working Range Φ mm:	20,25,32,40
Suit Material :	PP-R/PB/PE/PVDF
Net Weight(Set):	5.05KGS
PCS/Carton:	4PCS
N.W/Cartons:	17.30KGS
G.W/Cartons:	18.30KGS
Cartons Size:	49x43.5x20CM

Including the following accessories

- 1PC Fusion Welding Machine
- 1PC Floor Stand
- 1PC Metal Case
- 1PC Bag of Bolts and Hex Key Wrench
- 1PC Table Mounting Clamp (Optional)
- Sockets D20、 D25、 D32、 D40

*Las imágenes mostradas en este catálogo son referenciales y pueden variar del producto real.